

ERIE RAILROAD COMPANY

WESTERN DISTRICT

Marion Division

Time Table No. 60

Effective 2.01 A.M.

SUNDAY, APRIL 27, 1958

FOR EMPLOYEES ONLY

CENTRAL STANDARD TIME

60

**THINK!
THEN
ACT
SAFELY**

W. M. Wiarda
Assistant Superintendent

F. E. Navin
Superintendent

J. M. Moonshower
Assistant General Manager

J. P. Allison
General Manager

**SPECIAL INSTRUCTIONS
RULES OF THE OPERATING DEPARTMENT
EFFECTIVE NOVEMBER 30, 1952**

STANDARD CLOCKS.

Marion	}	Manifest Yard Office Terminal Building Kenton Avenue Westward Hump Office Engine Dispatchers' Office
Huntington	}	Train Dispatchers' Office Yard Office
Hammond		Yard Office

TIME TABLES.

Trains operating over another railroad will be subject to rules, special instructions and timetables of that railroad. Normal operation involves operating over the Chicago and Western Indiana Railroad between Hammond and Chicago.

Between Griffith and Hammond the tracks of the C. & O. R. R. and Erie will be operated as joint double track. Erie R. R. rules and time table will govern.

SIGNS. Additional to Rule 6.

B. Stop on signal to pick up passengers for Chicago.

C. Stop to discharge passengers from Chicago and receive passengers for Youngstown and east.

K. Stop daily except Saturdays and Sundays to pick up mail clerk. Flag stop Saturdays and Sundays.

M. Reduce speed to 40 miles per hour to discharge U. S. Mail, daily except Sundays.

Q. Reduce speed to 30 miles per hour to discharge U. S. Mail.

R. Reduce speed to 50 miles per hour to discharge U. S. Mail, daily except Sundays.

Trains scheduled to make flag stops at stations where no employe is on duty to give the necessary signal, will approach such points prepared to stop and will come to a full stop if there are any persons on the platform.

GENERAL SPEED RESTRICTIONS.

	Miles per Hour.
Passenger trains on tangent track	75
Passenger trains on curved track not otherwise restricted	70
Express and equipment trains with freight cars	50
Freight trains	50
Loaded cars carded Form 5432	30
All classes of yard engines, when operating as a single unit running light	25
All classes of road engines, including road switchers, when operating as a single unit running light	35
Yard engines, Classes SA (except SA-3), SB, SE, MSA and MSL, when operating or being towed in train	40
Special Mechanical Department instructions will govern the	

movement of yard engines Classes SA-3 and SG when operated light or being towed in train.

Trains hauling dead steam engine unless otherwise provided .. 20

Trains hauling wrecking derrick 30

Trains hauling 8-wheel swivel truck cranes, steam shovels and other similar pivoted machinery 30

The pivoted machinery listed immediately above is to be hauled on the rear of trains, not more than 15 cars from caboose.

Trains handling spreader cars 30

Spreader cars will be handled with blades in trailing position unless otherwise authorized by Superintendent.

Conductors will notify engineers before leaving terminals whether or not such equipment in train, and engineers will not leave terminals until so notified.

All trains entering or leaving sidings or yards, passing from double to single track or single to double track or through cross-overs, except as otherwise provided 10

All trains passing through No. 15 cross-overs at the following locations: Eastward and Westward, HN Tower, SJ Tower, DA Tower, Kingsland, Bolivar, Newton, Wilders and Kouts; Westward Griffith, Eastward Griffith C & O trains only, Eastward HY Tower 30

All trains and engines entering the sidings at Manitou, Delong and the east end of Rochester siding under signal indication, Rule 283, Figure A or Rule 286, Figure A, Rules of the Operating Department, may operate at a speed not to exceed forty (40) miles per hour through turnouts.

All trains and engines leaving the east or west ends of Manitou siding, east end of Rochester siding, east or west end of Delong siding under Signal indication Rule 287, Figure B, Rules of the Operating Department, may operate at a speed not to exceed forty (40) miles per hour through turnouts.

All trains and engines entering or leaving west end of Rochester siding may operate at speed prescribed by signal indication displayed at west end of siding.

FIRST SUB-DIVISION.

(Between C. & O. R. R. Crossing, Marion, and Huntington Station)

Curves 1 and 2, Marion Yard, MP 0.34 to MP 0.48, eastward track 35

Curve 3, Marion Yard, MP 0.48 to MP 0.49, westward track 25

Curves 4 and 5, MP 0.68 to MP 1.05 eastward track 40

Curves 6, 7, 10 and 11, MP 2.10 to MP 3.53, eastward track 60

Curves 8 and 9, MP 2.42 to MP 2.52, westward track 60

Curve 24, SJ Tower, M. P. 50.75 to MP 51.00, eastward and westward tracks 60

Between Reese Ave., Lima and Metcalf St., Lima, eastward and westward tracks 40

All trains over crossing frogs and curves between MP 79.20 and MP 79.45 at Ohio City, eastward and westward tracks 60

Curve 38, East of Decatur, MP 95.64 to MP 95.89 eastward and westward tracks 60

Curve 46, East of Huntington, MP 124.86 to MP 125.35 eastward

track 50

Curve 46, East of Huntington, MP 124.85 to MP 125.34 westward track 60

SECOND SUB-DIVISION.

(Between Huntington Station and State Line Tower)

Curve 47, West of Huntington, MP 126.77 to MP 127.04, eastward and westward tracks 30

Curve 48, West of Huntington, MP 127.29 to MP 127.49, eastward and westward tracks 40

Curve 49, West of Huntington, MP 128.47 to MP 128.75 eastward track 60

Curve 49, West of Huntington, MP 128.49 to MP 128.74 westward track 50

Trains moving from double to single track or from single to double track, AN-Akron, MP 158.60 70

Trains moving on Main Track or moving To or From Siding, GR-Pershing, MP 171.79 70

Trains moving from double to single track or from single to double track, AD-Aldine, MP 192.97 70

All trains over Railroad Crossings at North Judson, westward track 45

All trains over Railroad Crossings at North Judson, eastward track 55

All trains over Railroad Crossings at Griffith, westward track 45

All trains over Railroad Crossings at Griffith, eastward track 40

All trains over street crossings between 173rd Street and 165th Street, Hammond, Indiana 50

All trains between Douglas Street and 165th Street, Hammond 40

All trains between Hohman Avenue and Douglas Street, Hammond 25

All trains through interlocking limits at Michigan Central Crossing, Hammond 20

All trains through interlocking limits at Hammond Drawbridge 20

CLEARING OF TRAINS.

First Class trains will not leave Marion or Huntington without Clearance Form A.

First Class trains will not leave Dearborn Station, Chicago, without combined Erie-C&WI Clearance Form 902.

Eastward First Class trains originating at Chicago (except Dearborn Station), or Hammond, will not leave HY Tower without Clearance Form A.

No train, except First Class, will leave Marion (westward), Huntington (eastward and westward) Griffith (westward C. & O. trains only) or Hammond (eastward) without permission from train dispatcher.

Trains (except first class) leaving Huntington, Griffith, or Hammond through interlockings, will accept proceed signal as permission to leave.

MOVEMENT OF TRAINS.

The only time a Diesel Locomotive can be considered as operating backward is when a multiple unit road Diesel is operating with a blind unit or blind end ahead.

When light movements are made with multiple unit Diesel Locomo-

tives equipped with double end control, the locomotive must be operated from the end in the direction that the movement is being made.

In multiple unit operation of Diesel Locomotives, the locomotive number will be displayed on the lead unit only.

Diesel Locomotives, Motor Cars, and roller bearing equipped freight and passenger cars must not be operated in water that is higher than the top of the rail.

SPECIAL ORDER BOOKS AND BULLETIN BOARDS.

Marion	}	Engine Dispatcher's Office
		Terminal Building
		Westward Hump Office
		Kenton Avenue
Lima	}	Freight Agent's Office
Huntington		Yard Office
Griffith		C. & O. Cabin
Hammond	}	HY. Tower
		Yard Office
Chicago	}	Dearborn Station, Train Dispatcher's Office
		51 Street Yard Office

TRAIN REGISTERS.

Marion	}	Terminal Bldg., first class trains.
		Westward Hump Office, except first class trains.
Huntington	}	Yard Office.
Hammond		Yard Office, except first class trains.
Chicago		51st St. Yard Office, except first class trains.
	}	Dearborn Station, Dispatchers' Office, first class trains.

Trains not scheduled to stop at stations at which train registers are located, may register by throwing off train register slip, except when displaying signals for a following section when train must stop and the conductor register in person. When registering trains write out in full the color of the signals displayed. When not displaying signals, write out in full, "No signals," sign name and initials and use no ditto marks. It will be the duty of the employe in charge of the register station at points where trains are authorized to throw off train register slips, to enter the information on the train register and preserve the slip.

SIDINGS.

	Car capacity	
	Based on 45 feet to the car allowing for engine and caboose.	
	Eastward	Westward
KN. Siding	163	0
Kenton	0	135
HD. Siding	79	0

	Eastward	Westward
KP. Siding	137	137
Spencerville	40	0
Ohio City	148	137
Kingsland	0	50
Markle	40	0
Manitou		307
Rochester		425
Delong		361
North Judson	0	138
Crown Point	139	94
Griffith	93	132

YARD LIMITS. Indicated by signs.

Marion	Lima
Huntington	Hammond

RULE 93 (a)

Movement may be made against the current of traffic through the following yard limits by train orders and no further protection under Rule 93 (a) need be afforded: Lima, Huntington east of crossover at WR Tower and west of crossover College Road.

RAILROAD CROSSINGS AT GRADE.

Except where interlocking or controlled signals are in operation, trains and engines must come to a full stop not less than 200 feet nor more than 800 feet from railroad crossings at grade in Ohio and not less than 40 feet nor more than 500 feet from railroad crossing at grade in Indiana.

CROSSOVER MOVEMENTS.

When necessary to enter upon main track or crossover from one main track to another, permission will be first obtained except in Marion and Hammond yards, crossovers between lead and westward main track Market Street, and between westward and eastward main tracks at west fueling station, and from track 25 to eastward main track, Huntington. This does not relieve enginemen and trainmen from protecting the movements as per Rule 99.

Permission to use main tracks or crossovers operated by interlockings will be given by signal indication.

INSTRUCTIONS GOVERNING CROSSOVER AND OTHER MOVEMENTS AT OHIO CITY.

When either eastward or westward trains are to be operated against the current of traffic from Ohio City, following procedure will govern:

Interlocking signals will be displayed at stop and train order indicating light will be displayed.

EASTWARD—Approaching trains will acknowledge this combination of signals and after receiving restricted speed signal may proceed into interlocking limits where operator will deliver necessary train order and permission to use crossover. Conductor will see that switches are properly lined after being used.

When restricted speed signal is displayed at eastward home signal, and train order indicating light is not displayed, trains will proceed looking out for instructions to enter siding.

WESTWARD—Trains will come to a stop to clear east switch of cross-over and trainman will call on phone located on outside of east end of tool house for instructions and permission to use crossover. After permission is given, train will then cross over and proceed into interlocking limits on proper signal indication where necessary train orders will be delivered. Conductors will see that switches are properly lined after being used.

SPRING SWITCHES.

Marion-Griffith

The pull-out switch connecting C. & E. lead with westward main track at west end of Marion Yard, and switch at east end of eastward passing siding at Griffith are equipped with spring switch stands set normal for main track movements. Trains or engines may pull out of these tracks to main track without opening or closing switch by hand.

Extreme care must be taken to prevent back-up movements, slack running out of trains, or taking slack over spring switch before forward movement is completed. If necessary to make such movements, switch must be hand operated.

The switch at west end Marion Yard is protected by a semaphore type signal located 4600 feet west of the switch to govern the movements of trains operating against the current of traffic on westward main track, and the switch at east end of eastward passing siding at Griffith is protected by approach lighted color-light dwarf signal located 8400 feet east of the switch to govern movement of trains operating against the current of traffic on eastward main track. These signals will indicate as follows:

Clear—Proceed over spring switch.

Approach—Proceed to point of switch, then stop, examine switch points and make certain points are properly set before proceeding. If found out of order, use hand-throw switch and restore to normal position after using, reporting condition immediately to the Superintendent.

Trains moving against current of traffic on clear indication will pass over spring switches with entire train at a speed not to exceed 20 miles per hour.

These switches are equipped with electric switch signals which indicate as follows:

Green—Switch points properly lined for main track movement. Proceed over spring switch in accordance with special instructions.

Red—Switch points not properly lined for main track movement. Trains moving on main track, stop and examine switch points, using hand-throw to correct alignment of switch, if necessary, and proceed only when switch is properly secured, reporting any improper conditions immediately to the Superintendent.

Trains authorized by train dispatcher to occupy main track, may proceed over spring switches without opening or closing the switch by hand when switch signal displays "Green" indication.

If electric switch signal displays "Red" indication, switch must be

reversed by hand before movement is made and restored to normal position after entire train has passed.

These switches are also equipped with switch key-operated color light dwarf signals:

1. To operate dwarf signal, a member of crew will first secure permission from train dispatcher and then operate signal by inserting switch key in switch key operated controller located adjacent to switch, turning key to right as far as possible and remove key.
 - a. When approach circuit is not occupied, signal will immediately display proper indication to leave siding.
 - b. With approach circuit occupied, signal will display proper indication to leave siding after a time interval of four minutes.
2. If the intended movement out of the siding is not made after the controller has been actuated, signals must be restored to normal position by operating push-button at key controller.

RULES GOVERNING AUTOMATIC BLOCK SIGNAL SYSTEMS, EFFECTIVE NOVEMBER 30, 1952.

Automatic Block Signal System Rules will govern between Marion and Hammond.

SUPERIORITY OF TRAINS.

Trains operating in automatic block signal districts governed by telephone train order signals, may run with the current of traffic upon signal indication, which signal indication supersedes time table superiority.

POINTS WHERE INTERLOCKING RULES ARE IN EFFECT

Rules 605 to 672 inclusive, Rules of the Operating Department Effective November 30, 1952.

HN Tower	Bolivar
SJ Tower	Newton
BY Tower (B & O Jct.-Lima)	AH Tower (PRR-No. Judson)
Ohio City	Kouts
DA Tower	Griffith
Kingsland	ND Tower
WR Tower	HY Tower
	Hammond Drawbridge

Except at the following points, in the direction specified, where Traffic Control System Rules are in effect:

Bolivar Westward	Kouts Eastward
Newton Eastward	Griffith Westward
	HY Tower Eastward

POINTS WHERE INTERLOCKING SIGNALS ARE USED AS TRAIN ORDER SIGNALS.

See Rule 221, Rules of the Operating Department effective November 30, 1952.

HN. Tower	Bolivar
SJ. Tower	Newton
Ohio City	Delong
DA. Tower	Kouts
Kingsland	HY. Tower
WR. Tower	

THE USE OF MEDIUM APPROACH SIGNALS AT SPECIFIED LOCATIONS IN CONNECTION WITH RULE 221, RULES OF OPERATING DEPARTMENT, EFFECTIVE NOVEMBER 30, 1952.

In connection with Rule 221, Rules of the Operating Department, effective November 30, 1952, at the following locations: HN Tower (westward), SJ Tower, DA Tower, Kingsland, Bolivar (eastward), Newton (westward), Kouts (westward), after the train order has been transmitted and made complete operators may line up the route and display a medium approach indication without first waiting for the approaching train to acknowledge the combination of signals. This applies only when medium approach signal indication is to be displayed.

No train or engine will proceed on opposing track without having received necessary train orders and clearance forms.

TELEPHONE TRAIN ORDER SIGNALS

EASTWARD

Auto.
Sig. Location
728-2 Decliff
752-2 McGuffey
761-2 HD Siding
772-2 KP Siding
783-2 Spencerville
805-2 Wren
835-2 Markle
845-2 Huntington
870-2 Disko
950-2 Crown Point

WESTWARD

Auto.
Sig. Location
717-1 Kenton Ave., Marion
728-1 Decliff
752-1 McGuffey
760-1 HD Siding
771-1 KP Siding
781-1 Spencerville
795-1 Ohio City
805-1 Wren
835-1 Markle
841-1 Huntington
870-1 Disko
915-1 North Judson
937-1 Boone Grove
948-1 Crown Point
956-1 Griffith

REMOTE CONTROL INTERLOCKINGS

KN Tower, Kenton	Eastward & Westward
AN-Akron	Eastward
AD-Aldine	Westward
Wilders	Eastward

1. When movement is to be made at the above remote controlled interlockings in the direction specified only with the current of traffic and proper signal indication cannot be displayed, a member of the crew will call the operator or dispatcher and request permission for the move.
2. Instructions or permission received must be repeated to Train Dispatcher or Operator stating name and occupation of employee and train or engine identification.
3. After permission has been received, the movement through the interlocking may be made without signal indication at restricted

speed to the next signal, after member of crew has ascertained that switches are properly lined for their movement.

4. Permission received from the Train Dispatcher or Operator will be acted upon in lieu of Clearance Form B.

UNATTENDED INTERLOCKINGS

During the hours that the interlockings are closed, the following instructions will govern except they do not apply at Bolivar for westward trains or at Newton for eastward trains.

(1) The home signals governing movements through the interlocking with the current of traffic will be set to display "Clear" indication before the operator closes the tower. Dwarf signals will be set to indicate "Stop."

(2) When the interlocking signals display "Stop" for a train or engine during the hours the towers are closed, a member of the crew will immediately call Train Dispatcher and request permission to make the desired move.

(3) After permission is received from Train Dispatcher, the movement through the interlocking may be made without signal indication when preceded by a flagman, after a member of the crew has ascertained that signals governing other railroads are in "Stop Position", and that switches are properly lined for the movement.

(4) Permission received from Train Dispatcher for the move will be acted upon in lieu of Clearance Forms A and B.

TRAFFIC CONTROL SYSTEMS

OPERATING INSTRUCTIONS

The following territories are equipped with automatic block signal system upon which is superimposed manual control of certain signals and switches.

Eastward and Westward tracks between Bolivar and Newton (not including interlocking Bolivar Eastward and interlocking Newton Westward). Controlled by the operators at Bolivar and Newton.

Territory between AN-Akron and AD-Aldine. Controlled by the Dispatcher at Huntington.

Eastward and Westward tracks between Wilders and Kouts (not including interlocking Wilders Eastward and interlocking Kouts Westward). Controlled by the operators at Kouts.

Eastward and Westward tracks between Griffith and HY Tower (not including interlocking Griffith Eastward; interlocking ND Tower, High- and, Eastward and Westward; and interlocking HY Tower Westward). Controlled by operators at Griffith and HY Tower.

In the above mentioned territory, trains or engines will be governed by block signals whose indications will supersede the superiority of trains for both opposing and following movements on the same track.

1. When switching movements are to be made over switches that are signaled and equipped with power operated switch machines, an understanding must be had with the Train Dispatcher or operator who will advise working limits on main track and time in which switching may be done. When necessary to hand operate a power operated switch machine special instructions posted at the location will be followed.

2. When a train is delayed after a proceed signal has been displayed for it, the Train Dispatcher or operator must be notified promptly as to the cause and probable duration of the delay.
3. When a train is stopped by a STOP signal and there is no evidence of an approaching train, member of crew will immediately get in touch with Train Dispatcher or operator.
4. A train or engine must not make a reverse movement after accepting a CONTROLLED signal for straight away movement, except under flag protection or when movements are being made in accordance with Paragraph numbered 3.
5. Trains stopped or delayed after passing a distant signal displaying "CLEAR" must approach the CONTROLLED signal expecting to find that signal displaying its most restrictive indication.
6. Manitou, Rochester and Delong sidings are track circuited and protected by signals and may be used in either direction on signal indication.
7. A white light known as "Maintainers Call Signal" is located on instrument houses at KN, AN-Akron, MU-Manitou, RS Tower, GR-Pershing, Delong, MY-Monterey, AD-Aldine and Wilders. Train crews working in the vicinity and observing this signal lighted will immediately call the Train Dispatcher as this signal may be used on occasion to call train employees to telephone.
8. In all other respects Rules of the Operating Department effective November 30, 1952 will govern.

ELECTRIC SWITCH LOCKS

Lima

Westward main track switch leading to Dunn Coal Co. track, Lima is equipped with an electric lock.

A hand thrown derail on Lima Locomotive Works lead located just west of B&O track is equipped with electric lock.

Permission must be secured from the B&O R.R. operator before using the above switch or derail.

Rochester—Leiters—Delong—Monterey

The main track switches at Rochester, Leiters, Delong and Monterey are equipped with electric switch locks controlled by the Train Dispatcher. Before using these switches permission must be secured from the Train Dispatcher, who will unlock the electric lock.

Athens—Ora—Bass Lake

The main track switches at Athens, Ora and Bass Lake are equipped with electric switch locks controlled by key operated time controller. A portion of train must occupy a short track circuit to effect release of switch lock. Instructions relating to handling of switches are posted in telephone booth at these locations.

Griffith

The switch to the Michigan Central Interchange is equipped with electric lock. Permission must be secured from the leverman at Griffith Tower before using this switch.

HY Tower

The switch from the eastward main track to C&O Industrial District is equipped with an electric lock. Permission must be secured from the operator at HY Tower before using this switch.

Hammond

The switch from the westward main track to the EJ&E, just east of State Line Interlocking, is equipped with an electric lock. Permission must be secured from the leverman at Hammond Drawbridge before using this switch.

SPECIAL INSTRUCTIONS GOVERNING AUTOMATIC CROSSING PROTECTION

Highway crossing protection operating circuits at certain locations are arranged for fast and slow speed trains. At certain other locations automatic cut out circuits have been installed to prevent gates being lowered or protection operating continuously while trains are switching in the near vicinity of the crossing. The following instructions will govern:

Elgin

The highway crossing over State Route 81, located at MP 72.27, west of Elgin, is equipped with automatic short arm gates. Both crossover switches and elevator spur track at Elgin are equipped with automatic cut outs, which will permit gates to rise when switches are thrown in reverse if there are no other trains occupying the flasher circuits. If automatic cutouts have been actuated, westward trains will approach State Route 81 crossing prepared to stop if the gates are not lowered.

Decatur

The highway crossing of State Route No. 33, Mercer Avenue, Decatur, Indiana, is protected by automatic gates.

Crews switching and opening the switch from the Eastward main track to the house track and the switch from the Westward main track to the east spur or either of the switches of the crossover between the Eastward and Westward main track at Decatur Freight House will release the gates and permit them to rise, if there are no other trains occupying the flasher circuits.

Westward trains stopping and cutting away from their train east of Mercer Avenue and then proceeding over crossing with engine or part of their train will cause gates to rise as soon as the engine or cars have proceeded beyond the Westward home signal at DA Tower.

After switching moves have been completed and switches closed trains or engines must pull up to the crossing, stop and wait for the gates to re-lower before proceeding over the highway crossing.

Kingsland

Eastward trains operating on either track at a speed of 25 miles per hour or less passing through Kingsland interlocker must not exceed 25 miles per hour until after passing State Road No. 1, located at MP 108.75.

Rochester—U. S. Highway 31 (Main Street)

U. S. Highway 31 (Main St.) is protected by automatic gates. Trains switching on main track or eastward trains making station stop at Rochester station will approach U. S. 31 crossing prepared to stop if gates are not lowered. Trains switching on main track at Armour's Switch or Elevator Switch and moving westward will approach U.S. 31 crossing prepared to stop if gates are not lowered.

Eastward trains waiting or delayed more than 5 minutes in Rochester Siding in vicinity of Rochester station will approach U. S. 31 crossing prepared to stop if gates are not lowered. Eastward trains leaving

rear end of train in Rochester Siding while switching will leave rear of train west of "Gate Start" sign located approximately 1100 feet west of Fulton Street so that gates will raise while engine is switching.

Rochester—Fourth Street

Trains switching in NKP Interchange Switch in Manitou Siding will stop flashers at Fourth Street and must not proceed over Fourth Street Crossing until flashers are again operating.

Eastward trains switching in Armour's Switch on main track will stop flashers at Fourth Street and must not proceed over Fourth Street crossing until flashers are again operating.

Leiters

When crews open the switch to the switching track and if their train occupies the main track east of the switch, the flashers will stop working.

After the switch has been closed and Westward trains proceed the flashers will again commence. Trains which have cut out the flashers will not exceed a speed of 10 miles per hour until engine has passed Main Street crossing.

Delong

State Route 17 is protected by automatic flashers. Westward trains opening the switch for the interchange track will cause the flashers to stop and they will not again commence until the switch has been closed and the train proceeds over it. Trains having stopped the flashers will not exceed a speed of 25 miles per hour until engine has passed over State Route 17.

Monterey

The Walnut Street crossing at Monterey, Indiana, is protected by automatic flashers, and the Washington Street crossing at Monterey, Indiana, is protected by automatic crossing bell.

When crews open either of the switches to the switching tracks and if their train occupies the main track east of the switch, the flashers and bell will stop working.

Trains which have cut out the flashers and crossing bell will not proceed over the crossing until the flashers at Walnut Street and the crossing bell at Washington Street are operating.

Ora

The Main Street crossing at Ora, Indiana, is protected by automatic flagmen.

When crews open the switch to the switching track and if their train occupies the main track east of the switch, the flagmen will stop working.

Trains which have cut out the flagmen will not exceed a speed of 10 miles per hour until engine has passed Main Street crossing.

Bass Lake

The highway crossing of U.S. 35, at Bass Lake, Indiana, is protected by automatic flashers.

When crews open the switch to the switching track and if their train occupies the main track east of the switch, the flashers will stop working.

Trains which have cut out the flashers will not proceed over the crossing until the flashers are operating.

Kouts

Automatic gates are in service on highway crossings for State Route No. 8 and State Route No. 49, Kouts, Indiana. Trains switching on the main tracks or stopping at Kouts station will approach these crossings prepared to stop if the gates are not lowered and proceed over the crossing only when the gates have lowered. Trains or engines will not stop or stand within the limits of the starting point unnecessarily.

Crown Point

Westward trains on Westward track, making station stop at Crown Point will not exceed a speed of 60 miles per hour until after passing State Road 55, located at MP 233.62.

Griffith

Automatic gates are in service and will operate when engines or cars enter upon short track circuit through Broad Street crossing at Griffith, Indiana, on Erie Railroad-Michigan Central Interchange track. Clearance posts placed a short distance from each side of Broad Street crossing mark the limit of the track circuit. All trains, engines or cars about to make a movement upon Broad Street Crossing on Erie-MC interchange track must stop short of Broad Street crossing with the lead portion of such train, engine or car upon the track circuit to operate the automatic gates, and may proceed onto the crossing only after automatic gates have lowered to stop highway traffic.

When cars are left in this interchange track they must not foul the track circuit as this will cause gates to be lowered continuously.

Hammond

Westward trains on Westward track splitting train and leaving cars on Westward main track will leave them east of circuit sign located approximately 600 feet east of 175th Street. In so doing, after head end has moved over crossings, gates will rise at 175th, 173rd and White Oak Avenue.

Switch to Woodmar Lumber Co. and switch to C&O Industrial District are equipped with automatic cutout. When trains or engines are switching at these locations and switch is reversed, gates will rise. Trains then moving over crossing in either direction will proceed cautiously and must not pass over crossing until gates have lowered.

Westward trains on Westward track, stopped, delayed, or running less than 10 miles per hour at Mile Post 245.00 just east of 175th Street, Hammond, Indiana, will approach 173rd Street and White Oak crossing cautiously and will not pass over crossing until gates are lowered.

TONNAGE RATINGS.

Train tonnage will be determined by the Chief Train Dispatcher.

Trains will be given maximum rating unless otherwise directed.

MISCELLANEOUS.

Unless otherwise instructed all trains and engines, except first class trains, arriving Huntington will not pass College Road Crossover, or crossover at east end of Yard A, without calling on telephone for instructions.

When a car is set out of a train at any point on account of a hot journal, trainmen will extinguish fire before leaving the car.

Powdered chemical known as Du-Gas, for extinguishing fires in hot boxes of freight cars, has been distributed to all locomotives and cabooses in through freight service, and should be used according to instructions on box.

CODE SIGNALS.

Employees must observe passing trains, and if any hot journals, defective brakes, defective running gear, flat wheels, etc. are observed, trainmen will be notified by use of following code:

Hot Journals:

By day—Hold nose with first finger and thumb of right hand and point down toward track with left hand.

By night—Hold lantern in hand by guard wires around the globe and swing in small verticle circle.

Connections Dragging

By day or night—give stop signal.

Car Door Swinging or About to Fall:

By day—Raise hand above head and hold it stationary.

By night—Same signal with lantern, in addition give stop signal.

Brakes Sticking:

By day—Shove hand in sliding movement from body.

By night—Same signal with lantern, in addition give stop signal.

Flat Wheels:

By day—Place palms of both hands together in horizontal position.

By night—Hold lantern at arm's length with globe in horizontal position.

All Clear:

By day or night: Proceed signal.

Care will be taken that the above code signals are not used with passing trains, as sign of greeting.

OVERHEAD CLEARANCES.

The clear space between the lowest signal line conductor and the surface of track rails at the following locations is less than 27 feet. Employees must not ride on top of freight cars at these locations:

Location	Mile Post
Laketon Asphalt Corp. private siding, Laketon	147.38
Winona R.R. interchange track, Akron	157.61
PRR interchange track, Delong	179.61
PRR interchange track, Kouts	213.76
Standard Oil Co. track, Crown Point	232.70

AUTOMATIC TRAIN STOP

See Rules 520, 520 (a) and 520 (b), Rules of the Operating Department effective November 30, 1952 and Progressive Examination Questions and Answers on the Operation of Diesel-Electric Locomotives, effective June 1, 1954.

Open inductors are now in service on engine dispatching track at Marion Diesel Shop.

Enginemen are required to take a brake application passing over the first of these inductors and to acknowledge passing over the other.

W. J. Donnelly, Train Master

W. E. Boh, Road Foreman of Engines

N. T. Emrick, Road Foreman of Engines

J. R. Michael, Chief Train Dispatcher

G. W. Brodbeck, Asst. Chief Train Dispatcher

W. E. Coffman, Asst. Chief Train Dispatcher

J. E. Aughinbaugh, Asst. Chief Train Dispatcher

FIRST SUB-DIVISION

Distance from Marion	Distance Between Stations	STATIONS AND SIDINGS	WESTWARD TRAINS			
			FIRST CLASS			
			1 Daily	5 Daily	9 Sunday Only	7 Daily Except Sunday
		Eastern Standard Time	A.M.	P.M.	P.M.	P.M.
.....	HOBOKENL Central Standard Time	8.30	7.15	11.45	11.45
0.0	0.0	MARIONL N P.R.R. C.&O.	1.46	11.14	5.48	7.14
3.5	3.5	MJ. CROSSOVER .	1.51	11.19	5.53	7.19
10.7	7.2	DECLIFF				
17.3	6.6	HEPBURN				
25.0	7.7	KENTON	Q 2.10	B 11.37	s 6.13	s 7.40
25.2	0.2	HN. TOWER ...N N.Y.C.				
32.3	7.1	FORAKER				
34.9	2.6	McGUFFEY				
38.1	3.2	ALGER				
42.3	4.2	HARRODS				
43.2	0.9	HD. CROSSOVER .				
51.0	7.8	S.J. TOWER ...N D.T.&I.	2.33	11.58	6.36	8.03
52.0	1.0	LIMA	s 2.44	s 12.01	s 6.50	s 8.17
54.5	2.5	KP. CROSSOVER .				
64.8	10.3	SPENCERVILLE .	2.58	12.12	7.03	8.30
71.8	7.0	ELGIN				
79.3	7.5	OHIO CITY ...N N.Y.C. N.K.P.	s 3.12	12.24	s 7.17	s 8.44
83.8	4.5	GLENMORE				
87.9	4.1	WREN				
96.0	8.1	DECATUR	s 3.35	12.38	s 7.36	s 9.05
96.3	0.3	DA. Tower ...N P.R.R.				
100.8	4.5	PREBLE				
105.8	5.0	TOCSIN				
109.3	3.5	KINGSLAND ...N N.K.P.	3.49	12.49	7.49	9.18
112.6	3.3	UNIONDALE				
117.8	5.2	MARKLE				
126.6	8.8	HUNTINGTON AN WAB.	4.06	1.05	8.05	9.35
		Central Standard Time	A.M.	P.M.	P.M.	P.M.

FIRST SUB-DIVISION

Distance from Huntington	Distance Between Stations	STATIONS AND SIDINGS	EASTWARD TRAINS		
			FIRST CLASS		
			8 Daily	6 Daily	2 Daily
		Eastern Standard Time	P.M.	A.M.	P.M.
.....	HOBOKENA Central Standard Time	10.20	7.25	5.55
126.6	0.0	MARIONAN P.R.R. C.&O.	2.28	2.02	10.45
123.1	3.5	MJ. CROSSOVER .	2.22	1.56	10.39
115.9	7.2	DECLIFF			
109.3	6.6	HEPBURN			
101.6	7.7	KENTON	M 204	C 1.36	s 10.14
101.4	0.2	HN. TOWER ...N N.Y.C.			
94.3	7.1	FORAKER			
91.7	2.6	McGUFFEY			
88.5	3.2	ALGER			
84.3	4.2	HARRODS			
83.4	0.9	HD. CROSSOVER .			
75.6	7.8	S.J. TOWER ...N D.T.&I.	1.42	1.14	9.40
74.6	1.0	LIMA	s 1.40	s 1.13	s 9.38
72.1	2.5	KP. CROSSOVER .			
61.8	10.3	SPENCERVILLE .	1.20	1.00	9.17
54.8	7.0	ELGIN			
47.3	7.5	OHIO CITY ...N N.Y.C. N.K.P.	1.08	12.48	s 9.03
42.8	4.5	GLENMORE			
38.7	4.1	WREN			
30.6	8.1	DECATUR	12.54	12.34	s 8.43
30.3	0.3	DA. TOWER ...N P.R.R.			
25.8	4.5	PREBLE			
20.8	5.0	TOCSIN			
17.3	3.5	KINGSLAND ...N N.K.P.	12.43	12.23	8.24
14.0	3.3	UNIONDALE			
8.8	5.2	MARKLE			
0.0	8.8	HUNTINGTON LN WAB.	12.27	12.06	8.07
		Central Standard Time	A.M.	P.M.	P.M.

SECOND SUB-DIVISION

Distance from Marion	Distance Between Stations	STATIONS AND SIDINGS Central Standard Time	WESTWARD TRAINS			
			FIRST CLASS			
			1 Daily	5 Daily	9 Sunday Only	7 Daily Except Sunday
126.6	0.0	HUNTINGTON LN WAB.	A.M. 4.16	P.M. 1.13	P.M. 8.15	P.M. 9.45
135.5	8.9	BIPPUS				
141.8	6.3	SERVIA				
144.3	2.5	BOLIVAR N.Y.C.	4.33	1.29	8.31	10.02
146.0	1.7	NEWTON P.R.R.				
146.6	0.6	LAKETON				
152.8	6.2	DISKO				
157.9	5.1	AKRON				
158.6	0.7	AN-AKRON				
167.9	9.3	RS. TOWER N.K.P.				
168.3	0.4	ROCHESTER	s 4.59	s 1.52	s 8.53	s 10.25
171.8	3.5	GR-PERSHING				
177.8	6.0	LEITERS				
179.7	1.9	DELONG P.R.R.	5.11	2.02	9.04	10.37
183.6	3.9	MONTEREY	M.....			
187.4	3.8	ORA				
193.0	5.6	AD-ALDINE				
199.4	6.4	NORTH JUDSON N C.&O. N.Y.C. P.R.R.	f 5.31	2.18	9.20	10.55
205.1	5.7	LOMAX				
206.3	1.2	WILDERS MONON				
213.7	7.4	KOUTS P.R.R.	R 5.46	2.31	9.34	11.09
220.0	6.3	BOONE GROVE				
232.9	12.9	CROWN POINT	s 6.08	2.46	9.51	11.27
240.2	7.3	GRIFFITH C&O EJ&E GT MC	6.15	2.53	9.59	11.35
243.6	3.4	ND. TOWER N.Y.C.				
246.8	3.2	HY. TOWER	6.23	3.00	10.08	11.43
248.3	1.5	HAMMOND MC NKP B&OCT MONON	s 6.30	s 3.05	s 10.20	s 11.55
269.5	21.2	CHICAGO LN	7.05	3.40	10.55	12.30
		Central Standard Time	A.M.	P.M.	P.M.	A.M.

SECOND SUB-DIVISION

Distance from Chicago	Distance Between Stations	STATIONS AND SIDINGS Central Standard Time	EASTWARD TRAINS		
			FIRST CLASS		
			6 Daily	2 Daily	8 Daily
142.9	0.0	HUNTINGTON AN WAB.	A.M. 11.56	P.M. 7.57	A.M. 12.17
134.0	8.9	BIPPUS			
127.7	6.3	SERVIA			
125.2	2.5	BOLIVAR N.Y.C.	11.40	7.40	12.00
123.5	1.7	NEWTON P.R.R.			
122.9	0.6	LAKETON			
116.7	6.2	DISKO			
111.6	5.1	AKRON			
110.9	0.7	AN-AKRON			
101.6	9.3	RS. TOWER N.K.P.			
101.2	0.4	ROCHESTER	s 11.19	s 7.17	K 1139
97.7	3.5	GR-PERSHING			
91.7	6.0	LEITERS			
89.8	1.9	DELONG P.R.R.	11.07	7.01	11.27
85.9	3.9	MONTEREY			
82.1	3.8	ORA			
76.5	5.6	AD-ALDINE			
70.1	6.4	NORTH JUDSON N C.&O. N.Y.C. P.R.R.	10.51	f 6.43	11.10
64.4	5.7	LOMAX			
63.2	1.2	WILDERS MONON			
55.8	7.4	KOUTS P.R.R.	10.39	6.29	10.59
49.5	6.3	BOONE GROVE			
36.6	12.9	CROWN POINT	10.23	s 6.11	10.43
29.3	7.3	GRIFFITH C&O EJ&E GT MC	10.17	6.02	10.36
25.9	3.4	ND. TOWER N.Y.C.			
22.7	3.2	HY. TOWER	10.10	5.55	10.29
21.2	1.5	HAMMOND MC NKP B&OCT MONON	s 10.06	s 5.51	s 10.24
0.0	21.2	CHICAGO LN	9.30	5.10	9.45
		Central Standard Time	A.M.	P.M.	P.M.

COMPANY SURGEONS—Dr. W. E. Mishler, Chief Surgeon, Cleveland, Ohio

Table showing rate of speed required per mile to equal a given number of miles per hour

Time per Mile	Miles per Hour
0 min. 48 sec.	75.00
0 min. 49 sec.	73.47
0 min. 50 sec.	72.00
0 min. 51 sec.	70.59
0 min. 55 sec.	65.45
1 min. 0 sec.	60.00
1 min. 5 sec.	55.38
1 min. 12 sec.	50.00
1 min. 20 sec.	45.00
1 min. 30 sec.	40.00
1 min. 42 sec.	35.29
2 min. 0 sec.	30.00
2 min. 11 sec.	27.48
2 min. 24 sec.	25.00
2 min. 40 sec.	22.50
3 min. 0 sec.	20.00
3 min. 25 sec.	17.56
4 min. 0 sec.	15.00
4 min. 48 sec.	12.50
6 min. 0 sec.	10.00

LOCATION	NAME	OFFICE	PHONE	RESIDENCE	PHONE
Marion	D. M. Murphy	132 E. Church St.	3-7182	666 Virginia Ave.	2-5069
Marion	Clovis J. Altmaier	286 S. Main St.	2-0155	669 Bexly Ave.	2-1604
Marion	E. L. Brady, Oculist	247 S. Main St.	2-0601	483 Vernon Hgts. Blvd.	2-0325
Marion	A. E. Morrison	344 E. Center St.	2-3545	663 Virginia Ave.	2-0832
Marion	J. S. Greetham, Oculist	313 Bradford St.	2-1096	386 Brightwood Dr.	2-1097
Marion	J. E. Imbody, Oculist	313 Bradford St.	3-2353	354 Bradford St.	3-1887
Kenton	R. G. Schutte	110 E. Columbus St.	21289	408 N. Main St.	5170
Lima	L. C. Thomas	405 Cook Tower	73451	1533 Shawnee Rd.	78161
Lima	J. M. McBride	405 Cook Tower	8-8481	808 Pears Ave.	8-1711
Decatur	Gerald J. Kohne	134 S. Third St.	3-2617	304 W. Adams St.	3-2996
Huntington	S. M. Casey	408 E. Market St.	479	408 E. Market St.	479
Huntington	Thomas James, Jr.	202 U. B. Bldg.	676	1044 Poplar St.	766
Huntington	M. G. Erehart, Oculist	232 W. Market St.	299	Maple Grove Road	866
Huntington	J. B. Evison	34 E. Washington St.	51	1362 Poplar St.	782
Huntington	R. D. Meiser, Oculist	612 N. Jefferson St.	236	1738 Cherry St.	1127
Huntington	William A. Clunie (Asst. Oculist)	323 W. Park Dr.	370	323 W. Park Dr.	1334
Rochester	Dean K. Stinson	816 Main St.	CA-3-3121	1318 Main St.	CA-3-5278
Rochester	C. L. Richardson	119 W. 8th St.	CA-3-2287	506 Pontiac St.	CA-3-2806
North Judson	J. R. Matthew	524 Lane St.	84	605 Keller Ave.	78
Kouts	Jack E. Dittmer	23 Lincoln Way	39611	Railroad Ave., Kouts	3745
Crown Point	Daniel E. Gray	Valparaiso, Ind.	82	Timber Lane, R.R. 1	1639
Griffith	R. J. Purcell	182 West North St.	Temple	300 N. Lafayette St.	Temple
Griffith	J. M. Siekierski	145 N. Griffith Blvd.	8-1340	445 N. Broad St.	8-2693
Hammond	C. A. McVey	5231 Hohman Ave.	Temple	252 Humpfer St.	Temple
Hammond	W. H. Howard	5231 Hohman Ave.	8-1340	6534 Forest Ave.	8-1300
Hammond	David S. Koransky, Oculist	7217 Indianapolis Blvd.	Westmore	7048 Forest Ave.	Westmore
Chicago	A. T. G. Remmert	166 W. Jackson Blvd.	1-1024	988 Elm St., Winnetka	2-1027
Chicago	E. J. Gallagher	753 E. 79th St.	Westmore	7806 Crandon Ave.	Westmore
Chicago	Virgil Wescott, Oculist	30 N. Michigan Blvd.	3-0068	Worchester House	1-3083
			Tilden	244 E. Pearson St.	1-9222
			4-5410		Hillcrest
			Wabash		S. Shore
			2-6434		8-3081
			Hudson		Superior
			3-2340		7-5847
			Dearborn		
			2-3127		

STATION LIST

For the use of Agents, Conductors and Others, for reporting movements of Trains, Locomotives and Cars.

FIRST SUB-DIVISION	SECOND SUB-DIVISION	
Marion	718 Bippus	853
Swan Creek	721 Servia	859
DeCliff	728 Boiivar	862
Hepburn	735 Newton	863
Kenton	743 Laketon	864
Foraker	750 Disko	870
McGuffey	753 Akron	876
Alger	756 Athens	881
Harrods	760 Rochester	886
Westminister	763 Leiters	895
Lima	770 Delong	898
Hercules Torpedo Spur	773 Monterey	901
Kemp	776 Ora	905
Spencerville	782 Bass Lake	908
Converse	786 Aldine	912
Elgin	789 North Judson	918
Ohio City	797 Lomax	922
Glenmore	801 Wilders	924
Wren	805 Clanricarde	927
Decatur	814 Kouts	932
Preble	818 Boone Grove	938
Tocsin	823 Palmer	944
Kingsland	828 Crown Point	951
Undiondale	830 Griffith	958
Markle	836 Highland	961
Simpson	840 H. Y. Tower	965
Huntington	844 Hammond	966
	State Line (E.J.E.)	967
	Hegewisch (C.&C.R.) Ill.	969
	112th St. (So. Deering) (C.S.L.)	972
	Pullman Jct. (95th St.)	975
	81st St. (C.&W.I.-Belt)	979
	Englewood (63d St.)	981
	51st St.	982
	47th St.	983
	40th St.	986
	22nd St.	9908
	18th St.	9909
	14th St.	9910
	Chicago (Dearborn Station)	987

INTERCHANGE POINTS IN FOREIGN YARDS

